

# VTH1550CHM IP Indoor Monitor



### **Technical Specification**

Model	VTH1550CHM
System	
Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS
Video	
Video Compression	H.264
Audio	
Audio Compression	G.711
Audio Input	All-direction Microphone
Audio Output	Built-in Loudspeaker
Bidirectional Talk	Support Dual-way Bidirectional talk
Display	
LCD Screen	7" 800x480, Capacitive
Operation Mode	
Input	Touch screen
Interface	
Alarm In	8
RS485	1
Network	
Ethernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP
General	
Memory Slot	Micro SD, Max 32GB

## Features

- 7" TFT Capacitive touch screen
- $\cdot$  IPC surveillance
- $\cdot$  Alarm integration
- $\cdot$  Micro SD card optional, max 32GB
- · Record & Snapshot(SD card needed)





Installation	Flush
Power	DC 12V/ supply directly by VTNS1060A
Power Consumption	Standby $\leq$ 1.5W, Work $\leq$ 7W
Working Temperature	-10°C~+55°C
Relative Humidity	10%~90%RH
Dimensions	200.5mm×136.5mm×22.0mm
Weight	1.0Kg

## VTH1550CHM

### Dimensions

View Area





## Application

