

# 32 Inches Plastic Case LCD Monitor

### MW3232-V-K2



### **Features**

- Plastic casing, even lighter.
- New color management module delivers true to life colors.
- Ultra narrow bezel, ultra slim depth, light weight and elegant.
- Wide 178 viewing angles allow viewing from almost any direction.
- Automatic detection of signal cable connection.
- Stable structural design, highly durable.
- Easy pedestal assembly/disassembly. Flexible wall mount and pedestal mount, saving space.

## **Specifications**

Panel	Description
Panel Size	32"
Pixel Pitch (H x V) (mm)	0.36 x 0.36
Resolution	1920 x 1080
Color Support	16.7 M
Brightness (cd/m²)	300
Contrast Ratio	4000:1
Refresh Rate	75 Hz
Response Time (ms)	8
Viewing Angle (H/V)	Horizontal 178°, Vertical 178°

1







Display Size (mm)	698.40 x 392.85
Operation Hour	24/7
Interface	Description
Video Input	1 x VGA, 1 x HDMI
Audio Input	1 x Audio
Speaker	Description
Speaker	2 x 2 W
VESA	Description
VESA (mm)	100 x 100
Wall-mounted Thread	4-M4 Screw Holes, 8mm Deep
OSD	Description
Multi-Language	Polish, Dutch, Italian, German, Portuguese, Spanish, French, English, Simplified Chinese, Korean, Russian, Turkish
General	Description
Input Voltage	DC 12V, 3A
Typical Power Consumption (W)	<36
Standby Power Consumption (W )	<0.5
Product Dimensions (W x H x D) (mm)	712.54 x 422.96 x 61.60 (Excluding base) 712.54 x 517.14 x 199.64 (Including base)
Package Dimensions (W x H x D ) (mm)	784 x 512 x 144
Weight (Kg)	Net Weight: 4.1 Gross Weight: 6
Operating Temperature	0°C ~ 50°C
Operating Humidity	10% ~ 90% (No Condensation)
Storage Temperature	-20°C ~ 60°C
Storage Humidity	5% ~ 90% (No Condensation)
Standard	1 x HDMl Cable, 1 x Base, 1 x Adapter, 1 x Quick Guide
Optional Accessories	HB-4022-E




# **Dimensions**







## Interface



## **Ordering Info**

Product Model	Description
MW3232-V-K2	32 Inches Plastic Case LCD Monitor

#### Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

http://www.uniview.com

©2024 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

<sup>\*</sup>Product specifications and availability are subject to change without notice.

<sup>\*</sup>Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.