



DATASHEET TR-NS1105-60-4POE



TR-NS1105-60-4POE – is an unmanaged switch with 4 10/100 Mbps PoE portswith the ability to power up the connected devices power twisted pair.

Basic equipment

- Switch 1pcs.
- Datasheet 1pcs.

Warranty service

- Three - year warranty service from the date of sale.
- In case of the warranty card absence, the warranty period is determined from the date of sale.

Specification

Model	TR-NS1105-60-4POE	
Ethernet ports	5 x 10/100 Mbps (Base-TX)	
PoE Standards	Ports 1–4: IEEE802.3af/at/bt	
Maximum capacity per port	Total: 60 Bt Ports 1–3: up to 30 W	Port 4: up to 60 Bt
Power pinout via PoE	Ports 1–4: DC+: 1/2/4/5 DC-: 3/6/7/8	
Switching capacity	1 Gbps	
Transmission speed	0.744 Mpps	
Buffer size	1 MB	
MAC addresses table size	2000	
Stream management	Enabled by default	
Data transmission range	Up to 130 m	
Function	Autoadaptation	
PD Alive ¹	Supported. The port restarts 180 seconds after device connection loss	
Power	AC 90–240 V, 50–60 Hz	
Lightning protection	Standard mode 6kV Differential mode 4kV	
Electrostatic discharge protection	Air discharge 8kV Contact discharge 10kV	
Maximum power consumption	60 W	
Mounting	Desktop	
Working temperature	-30°C...60°C	
Permissible humidity level	10 – 90 %	
Weight, kg	0.24	
Dimensions (W xD x H), mm	140 x 65 x 34	

¹ For more details, see the user manual for the device.

DATE OF SALE

SERIAL NUMBER