. Since 1968



# **User Manual**





#### www.commax.com

COMMAX

COMMAX Co.,Ltd.

- · Thank you for purchasing COMMAX products.
- Please carefully read this User's Guide (in particular, precautions for safety) before using a product and follow instructions to use a product exactly.
- The company is not responsible for any safety accidents caused by abnormal operation of the product.



## 1. Warnings and Caution

To prevent fire or shock hazard, do not expose the unit to rain or moisture.

A This symbol is intended to alert the use to the presence of uninsulated **"dangerous Voltage"** within the product' s enclose that may be of sufficient magnitude to constitute a risk of electric shock to persons.


This symbol is intended to alert the use to the presence of important operating and maintemance (servicing) instructions in the literature accompanying the appliance



personnel.

2. Overview

#### Handset




3. Operation


#### [SUB UNIT]

- 1. Electric chime call.
- 2. Back call tone for visitor.
- 3. Hands free talk within 30cm.

#### [MASTER UNIT]

- 1. Lift up handset and talk when a call's coming.
- 2. Control a call sound with volume control.
- 3. Door release button able to open the door.





- 1. Non polarity wiring with Sub Unit(1) and Master Unit (2).
- 2. Door Release(3) should be provided with additional power source.

6. Specification

Model	DP-2S
Power Source	100/110/120/220/230/240V~, 50/60Hz
Consumption Power	4.5W(MAX)
Distance	100m( Ø0.65mm), 150m( Ø0.8mm)
Wiring	Call : 2-wire, Door Release : 2-wire(Ø 1.6mm Copper wire)
Dimension(mm)	108(W)°X210(H)°X61.4(D)mm
Weight(g)	640g



### COMMAX Co.,Ltd.

513-11, Sangdaewon-dong, Jungwon-gu, Seongnam-si, Gyeonggi-do, Korea Int'l Business Dept. : Tel.; +82-31-7393-540~550 Fax.; +82-31-745-2133 Web site : www.commax.com

Printed In Korea / 2016.04.105