




DATASHEET
TR-NS1410-120-8PoE



TR-NS1410-120-8PoE is an unmanaged switch with 8 x 10/100/1000 Mbps PoE ports with the ability to power up the connected devices through twisted pair.

Basic equipment:

- Switch 1pcs.
- Power cord with adapter 1pcs.
- User Manual 1pcs.
- Device datasheet 1pcs.

Specification:

| | | |
|---|---|------------------------------------|
| Model | TR-NS1410-120-8PoE | |
| Ethernet ports | 8 x 10/100/1000 Mbps (Base-T) 2 x 10/100/1000 Mbps (Uplink, Base-T) | |
| PoE Standards | Port 1: IEEE802.3af/at/bt | Ports 2-8: IEEE802.3af/at |
| Maximum capacity per port | Total: 120W Port 1: up to 90W Ports 2-8: up to 30W | |
| Power pinout via PoE | Port 1: DC+: 1/2/4/5 DC-: 3/6/7/8 | Ports 2-8: DC+: 1/2 DC-: 3/6 |
| Switching capacity | 20 Gbps | |
| Transmission speed | 14.8 Mpps | |
| Buffer size | 2.5 MB | |
| MAC addresses table size | 2000 | |
| Stream management | By selection | |
| Function | Normal mode VLAN CCTV | |
| PD Alive¹ | Supported. The port restarts 175 seconds after device connection loss. | |
| Power consumption | 100-240V AC power adapter | |
| Lightning protection | Standard mode 6kV Differential mode 2kV | |
| Electrostatic discharge protection | Air discharge 10kV Contact discharge 8kV | |
| Maximum power capacity | 120W | |
| Working temperature | -10°C...55°C | |
| Permissible humidity level | 0 – 90 % | |
| Weight, kg | 0.8 | |
| Dimensions (WxDxH), mm | 210 x 150 x 35 | |

¹ For more details, see the user manual for the device.

Warranty service:

- Three - year warranty service from the date of sale.
- In case of the warranty card absence, the warranty period is determined from the date of sale.

DATE OF SALE

SERIAL NUMBER