

## DS-KH8380-TE1 8 Series Indoor Station



- 7-inch TFT touch screen with 1024 × 600 resolution
- Convenient Hik-Connect APP MobileControl
- Receive calls, open the door and live view remotely
- Standard IEEE802.3at PoE power supply
- Supports up to 16 indoor extensions linkage
- Elevator access control
- Supports surface and flush mounting

## ▪ Specification


System parameters	
Operation system	Embedded linux operation system
ROM	32 MB
RAM	128 MB
Processor	Embedded high performance processor
Display parameters	
Screen size	7-inch
Operation method	Capacitive touch screen
Type	Colorful TFT
Resolution	1024*600
Video parameters	
Lens	/
Resolution	/
FOV	/
Wide dynamic range (WDR)	/
Video compression standard	H.265 ; H.264
Focal length	/
Audio parameters	
Audio input	1 built-in omnidirectional microphone
Audio compression standard	G.711u、 G.711a、 Opus、 AAC-LD、 AAC-LC、 G.726、 G.722.1
Audio output	1 built-in loudspeaker
Audio compression bitrate	16、 32、 64 Kps
Audio quality	Noise suppression and echo cancellation
Volume adjustment	Adjustable
Capacity	
Message capacity	TF card inserted: 200 captured pictures, 200 alarm records Without TF card: 2 MB RAM for picture storage; The storage number is decided by the picture size, 200 alarm records
Notice capacity	200
Linked network camera capacity	16
Linked indoor extensions capacity	16
Linked doorphone capacity	/
Network parameters	
Network protocol	TCP/IP, SIP, RTSP
Wi-Fi	/
Wireless network	1 RJ-45 10/100 Mbps self-adaptive
Bluetooth	/
3G/4G	/
Zigbee	/
Device interfaces	
Alarm input	8
Network interface	1 RJ-45 10/100 Mbps self-adaptive
TAMPER	/

RS-485	/
USB	/
TF card	Support TF card, up to 128 G
Alarm output	/
Lock control	/
Debugging port	1
Relay	/
<b>General</b>	
Installation	Flush mounting, surface mounting, table mounting
Indicator	/
Weight	Without package: 366.7 g (0.808 lb)
Protective level	/
Working temperature	-10 °C to 50 °C (14 °F to 122 °F)
Working humidity	10% to 90% (no-condensing)
Dimension (W × H × D)	178.4 mm × 126.4 mm × 21.8 mm (7.02" × 4.98" × 0.86")
Battery	/
Power supply	IEEE802.3at, Standard PoE, 12 VDC, 1.5 A
Application environment	Indoor
Power consumption	≤ 12 W
Language	English, Arabic, French, Russian, Spanish, Spanish (Latin America), Italian, German, Polish, Turkish, Portuguese, Portuguese (Brazil), Uzbek, Kazakh, Czech, Hungarian, Dutch, Romanian, Bulgarian, Ukrainian, Croatian, Serbian, Greek, Lithuanian, Estonian, Latvian, Norwegian, Danish, Slovenian, Slovak, Hebrew, Swedish, Finnish, Mongolian, Vietnamese, Traditional Chinese
Material	Plastic casing

## ▪ Available Model

DS-KH8380-TE1

## ▪ Dimension



- Accessory
- Optional

DS-KABH8380-T	DS-KABH8380-G
	

- Installation Methods

Inclined Ceiling Mounting DS-KABH8380-T	In-Ceiling Mounting DS-KABH8380-G
---	--------------------------------------

# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

