

# UV-NVR824-256R

NVR for IP cameras

Pro range

256 CH video | 12 Mpx

Bandwidth 768 Mbps

Supports 24 hard drives | RAID

Redundant power supply



Uniview

NVR for IP cameras

Pro range

256 CH

768 Mbps bandwidth supported

Maximum resolution 12 Megapixel

256 remote users

Alarms

Audio

Output 2 x HDMI 4K and VGA

Space for 24 HDD up to 10 TB

RAID function

2 x miniSAS

RS232, RS485, 2 x USB3.0, 2 x USB2.0

4 x RJ45

Output 12 V

Optional redundant power supply

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

# Specifications

<b>Brand</b>	Uniview
<b>Range</b>	Pro
<b>Inputs for IP cameras</b>	LAN port up to 256 channels
<b>IP compatible cameras</b>	UNIVIEW, ONVIF
<b>Video outputs</b>	2 HDMI 4K, 1 VGA
<b>Video compression format</b>	Ultra265 / H.265 / H.264
<b>Resolution HDMI display</b>	1920x1080p@60Hz, 1920x1080p@50Hz, 1600x1200@60Hz, 1280x1024@60Hz, 1280x720@60Hz, 1024x768@60Hz
<b>Total bandwidth</b>	768 Mbps downstream / 768 Mbps upstream
<b>Main Stream recording</b>	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
<b>Bidirectional audio</b>	1 input / 1 BNC output
<b>Alarms</b>	24 Inputs / 8 Outputs
<b>Intelligent functions</b>	People Counting, Face Detection, Human Body Detection, Intrusion Detection, Line Crossing, Audio Detection, Scene Change, Blur Detection, Auto Tracking, Object Removed, Object Left Behind
<b>SIP Channels</b>	24 channels
<b>Facial recognition channels</b>	24 channels
<b>LPR Channels</b>	8 channels
<b>Internal memory</b>	24 SATA HDD 3.5" up to 10 TB (not included)   2 x miniSAS
<b>Storage technology</b>	RAID function 0/1/5/6/10/50/60 and Hot Spare function N+1
<b>Communication</b>	2 x USB 3.0 / 2 x USB2.0 / 4 x RJ45 (Ethernet) / 1 x RS232 / 1 x RS485
<b>Remote users</b>	256
<b>Remote access</b>	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
<b>Power</b>	AC 100 ~ 240V (Redundant power supply optional)   DC output 12V
<b>Dimensions / Weight</b>	533mm x484.6mm x 175.5mm / ?12.5 Kg