

Quick Start Guide

Model: DL30Z

Version: 1.0

How to pair the Gateway and Smart Lock with the ZSmart App?

Step 1. Download the ZSmart App

- 1 Search for the "ZSmart" App in iOS App Store or Google Play Store, or scan the QR code to download the App.
- 2 Open the "ZSmart" App, register and sign in to the account.



Step 2. Add the Gateway

- 1 Plug the Gateway into the outlet using the provided Power Adapter. Wait for a few seconds until the **red LED blinks rapidly**.
- 2 Open the ZSmart App. Tap the "+" button on the upper right corner of the interface, and then select "**Smart Lock / Wireless Gateway**" category.
- 3 Follow the on-screen instructions to connect the Gateway to 2.4GHz Wi-Fi network and complete the setup.

Note: The default pairing mode is **EZ Mode**. If the red LED blinks slowly, press and hold the **Reset** button for 5 seconds to make the red LED blink rapidly.

Step 3. Add the Smart Lock

- 1 Tap the "+" button on the upper right corner, and then select "**Smart Lock / DL30Z**" category to add to the Gateway.
- 2 Follow the on-screen instructions, and tap the "**Confirm**" button first.
- 3 Then program the Network Settings on the lock. The steps are as follows: Activate the lock -> Press the **0** and **#** keys to access the menu -> Verify the Administrator's identity -> Press the **9** and **#** keys first, and then **1** and **#** keys.



Now, you can manage the lock from anywhere via ZSmart App!

ZKTeco Industrial Park, No. 26, 188 Industrial Road,

Tangxia Town, Dongguan, China.

Phone :+86 769-82109991

Fax :+86 755-89602394

www.zkteco.com

